

ALMATEC PUMP AD50

2" METAL



MAX FLOW RATE: 400 LPM (105.7 GPM)

MAX PRESSURE: 7 BAR (100 PSI)

MAX DIAMETER SOLIDS: 14 mm (0.55")

MAX SUCTION LIFT CAPABILITY:

3 m (9.8') Dry, 9 m (29.5') Wet

WETTED HOUSINGS


Material	Ship Wt
Stainless Steel 316	29 kg (63.9 lbs)
Stainless Steel polished	29 kg (63.9 lbs)

NON-WETTED HOUSINGS

Description	Material
Center Section	PA
Air Valve	PETP

ELASTOMER OPTIONS

Material	Temperature limits
EPDM™	-51.1 (-60) to +137.8 (+280) °C (F°)
PTFE	+4.4 (+40) to +104.4 (+220) °C (F°)
NBR	-12.2 (+10) to +82.2 (+180) °C (F°)



HOLLAND AIR PUMPS BV

De Scheper 260
NL 5688 HP OIRSCHOT
THE NETHERLANDS

PHONE

+31 (0)499 551 000

FAX

+31 (0)499 551 005

VAT

NL8033.13.123.B01

ING-BANK ACC

NL79 INGB 068 29 36 022

ONLINE

WWW.HOLLANDAIRPUMPS.NL
INFO@HOLLANDAIRPUMPS.NL

CHAMBER OF COMMERCE

ROTTERDAM 24.252.831